

The Malaysian Eagle Aerial Reconnaissance Vehicle (ARV)

Wan Izani Excelnet Sdn Bhd, Cyberjaya, Malaysia

Mark Gardner BAE SYSTEMS, Santa Monica, CA

June 2002

ADV3497







maintaining the data needed, and of including suggestions for reducing	llection of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar OMB control number.	ion of information. Send comments arters Services, Directorate for Information	regarding this burden estimate mation Operations and Reports	or any other aspect of the property of the contract of the con	nis collection of information, Highway, Suite 1204, Arlington
1. REPORT DATE 02 SEP 2003		2. REPORT TYPE N/A		3. DATES COVERED	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER	
The Malaysian Eagle Aerial Reconnaissance Vehicle (ARV)				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Excelnet Sdn Bhd, Cyberjaya, Malaysia; BAE SYSTEMS, Santa Monica, CA				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT lic release, distributi	on unlimited			
13. SUPPLEMENTARY NO See also ADM0016	otes 76, UAV 2002 confe	erence & Exhibition	, The original do	cument conta	ains color images.
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFIC	17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF		
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	UU	17	RESPONSIBLE PERSON

Report Documentation Page

Form Approved OMB No. 0704-0188





- To explain the reasons why Eagle 150 was selected as the platform for the Malaysian Aerial Reconnaissance Vehicle (ARV) Program and to highlight the benefits of having manned and unmanned operational capability
- To discuss the process by which Composite Technology Research Malaysia (CTRM), Excelnet Sdn. Bhd., and BAE SYSTEMS converted the Eagle 150 twin-seater aircraft into an ARV in less than 8 months.









Eagle-150B Aircraft











Why an Eagle-150B Aircraft?

Eagle-150 aircraft is a two-seater, single engine of a fully composite light aircraft.

- Certified by CASA, FAA and JAR.
- Handling qualities ideally suited for surveillance missions
 - Outstanding low speed control
 - Able to operate from short, unimproved runways
 - Stable in all flight regimes
- All composite structure
 - Low observable Corrosion resistance
 - High impact strength
 Long fatigue life
- Low life-cycle cost
 - Low operating and maintenance cost
 - Existing support for maintenance and spares in Malaysia









Eagle ARV









Why an Aerial Reconnaissance Vehicle (ARV)? EAGLE ARV

The main reason for developing an ARV is to obtain system flexibility to meet a variety of mission profiles for both manned and unmanned missions using the same aircraft.

Unmanned version applications and benefits

- For hazardous missions
 - Chemical or nuclear contaminant detection
 - Hostile and threat area operations
- For long endurance missions
 - Coastal water surveillance missions
 - Operations in remote areas







Manned version applications and benefits

- Able to operate in civil airspace
- Added situation awareness for surveillance missions
- Valuable for training purposes
 - Operational conversion for pilots
 - Mission rehearsal and tactics development
 - Providing a good low cost lead-in platform for more advanced UAVs
- Easy for rapid re-deployment as the ARV can be piloted to the new operational site







Missions of Eagle ARV

It is intended that the aircraft is able to provide a range of airborne military and commercial surveillance capabilities suitable for a broad spectrum of operational environments including:


- Battlespace command and patrol
- Coastal and border patrolling
- Off-shore monitoring of illegal trafficking and piracy
- Identification of water & air pollution sources
- Prevention of illegal logging
- Assisting in air, land and sea rescue operations
- Crowd and traffic surveillance and management
- Disaster area management and communications







Eagle ARV Equipment Installation












Aircraft/Flight Control Modifications



Aileron actuator installation



ARV Main flight control box



Rudder actuator







Eagle ARV Specifications and Performance

Air Vehicle Performance

Max Level Speed 133 knots 240 km/h

Cruise Speed 120 knots 216 km/h

Best Loiter Speed 65 to 75 knots 117 to 139 km/h

Stall Speed (Clean) 56 knots 101 km/h

Stall Speed (Full Flaps) 45 knots 83 km/h

Range (From GCS) 124 nm 200 km

Endurance 10 hrs

Ceiling Altitude 12000 ft 4877 m









Eagle ARV Specifications and Performance

Air Vehicle Dimensions

Wing Span 23 ft 6 in 7.163 m

Length Overall 21 ft 2 in 6.492 m

Height Overall 7 ft 7 in 2.324 m

Propulsion

Engine TCM IO 240-125 hp

Propeller Metal - McCauley

Crew Requirements

GCS 2

Support 6







System Features

The Eagle ARV system comprises three aircraft, a ground station and a remote receiving station.

The Eagle ARV's integrated surveillance system comprises of:

- A 15:1 continuous zoom color EO imaging sensor
- A spotter scope imaging sensor
- Third generation step-zoom FLIR

This equipment is integrated into a lightweight turret mounted in the underbelly of the aircraft. This provides the operator with an unobstructed 360 ° field of view.

All sensor data is recorded onto dual S-VHS recorders that allow the operator to replay previously recorded imagery.







Ground Control Station Features


- The Eagle ARV's Ground Control Station (GCS) is built into a single trailer, containing pilot and payload operator consoles. This includes a Data Exploitation and Mission Planning System which is capable of accepting up to 256 pre-planned waypoints, together with a microwave line-of-sight ground data terminal.
- The ARV is controlled in real time up to a distance of 200 km while flying a line-of-sight profile for up to 10 hours without re-fuelling. The GCS can send imagery data via a landline to a networked command center or to a remotely sited data distribution system.







The Ground Control Station













Problems Encountered

- Insufficient Air Regulations for fully autonomous/ unmanned flight. The Eagle ARV was issued a "permit to fly" under the "Military Experimental" category
 - To gain user's confidence for unmanned flight a Ballistic Recovery System (BRS) was added.
 - Added ATC voice relay and remotely tunable IFF
- Slight decrease in the ARV's performance. Higher than expected drag induced by the payloads has reduced the intended altitude and range.









THANK YOU





